# 7,000 LB. / 9,000 LB. STORAGE / SERVICE

LIFT

7,000 lb./9,000 lb. capacity and large 3" cylinder, one-piece diamond-plate runways and scratch-resistant powder coat paint.



#### Features:

- 7,000 lb./9,000 lb.
  lifting capacity
- Carriages completely enclosed for safety
- Aircraft quality cables rated at 14,500 lbs.
- 18 ½" wide runways formed with one piece ¾6" non-skid diamond plate
- Hydraulic pump available in 110 or 220 vac
- Easy operation—lock handle is located by power unit minimizing any bending or squatting
- Large 3" diameter cylinder is located safely under runway

-Options

Specifications	FP9K (Not Shown)	<b>FP7K</b>	FP7K-XLT (Not Shown)
Lifting capacity	9,000 lbs.	7,000 lbs.	7,000 lbs.
Overall length (to outside base plates)	175"	171"	190"
Total width (to outside base plates)	105 ¾"	112"	112"
Overall height	82"	84"	92"
Track length (without ramp)	165"	160"	180 3/4"
Track width	18 ½"	18 ½"	18 ½"
Rate of lift	90 sec.	90 sec.	100 sec.
Width between posts	94"	99"	100"
Maximum clearance under tracks	73"	65"	78"
Shipping weight	1,485 lbs.	1,485 lbs.	1,680 lbs.






## One-Step Caster Kit

Easy to install with no tools— simply pin them on, lower lift, casters automatically lift the columns; allows mobility with or without a vehicle; turn lift sideways to park two vehicles underneath.



## Solid Deck Option

Large storage area. Two diamond plate platforms drop between tracks for storage of snowmobiles, ATVs and garden equipment. Constructed of lightweight aluminum.



## **Aluminum Approach Ramps**

These lightweight ramps weigh only 18 lbs. each compared with the 53 lbs. of standard ramps.

### Stackable Poly Drip Trays, 3

Lightweight polyethylene; stackable: simply slide to back and stack! 8" or 12" widths.